

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
26 May 2006 (26.05.2006)

PCT

(10) International Publication Number  
**WO 2006/054828 A1**

(51) International Patent Classification:  
**B04B 5/02** (2006.01)

(21) International Application Number:  
PCT/KR2005/003065

(22) International Filing Date:  
15 September 2005 (15.09.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2004-0094893  
19 November 2004 (19.11.2004) KR

(71) Applicant (for all designated States except US): **HANLAB CORPORATION** [KR/KR]; 484-1, Dongpae-ri, Gyohaeup, Paju-si, Gyeonggi-do 413-833 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KIM, Hak Chul** [KR/KR]; 1512-103, Hanareum Apt., Sang 1-dong,

Wonmi-gu, Bucheon-si, Gyeonggi-do 420-752 (KR).  
**PARK, Chong Tae** [KR/KR]; 457-19, Shillim 4-dong, Kwanak-gu, Seoul 151-014 (KR).


(74) Agent: **NAM, Sang-Sun**; KAL Bldg., 3rd Floor, 41-3 Seosomun-Dong, Jung-Gu, Seoul 100-813 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: AUTOMATIC BALANCING CENTRIFUGAL APPARATUS BY FLUID COMPENSATION



(57) Abstract: The invention relates to an automatic balancing centrifugal apparatus by fluid compensation, which compensates a load imbalance among buckets holding samples by injecting a fluid into the buckets or sucking the fluid from the buckets, thereby simplifying the overall structure of the centrifugal apparatus, increasing the durability, and centrifuging a large quantity of samples under various high-speed rotation conditions smoothly. The automatic balancing centrifugal apparatus by fluid compensation comprises: rotors on which a plurality of buckets are mounted; a centrifuge motor for rotating said rotors; a load measurement mechanism, which is installed so as to lift and lower along the rotation trace of said buckets and which measures the load of said buckets while the restraint of the buckets is being released at the time of lifting; a position sensing mechanism for sensing whether or not each of said buckets is positioned right above said load measurement mechanism; a fluid compensation mechanism for injecting a fluid into said buckets or for sucking the fluid from the buckets; and a main control part for controlling the overall operations of each of said elements and for controlling said fluid compensation mechanism so that the loads of said buckets can become equal to each other.



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

## Description

# AUTOMATIC BALANCING CENTRIFUGAL APPARATUS BY FLUID COMPENSATION

### Technical Field

- [1] The invention relates to an automatic balancing centrifugal apparatus by fluid compensation, and particularly to an automatic balancing centrifugal apparatus by fluid compensation which is capable of compensating a load unbalance among buckets holding samples by injecting a fluid into the buckets or sucking the fluid from the buckets.

### Background Art

- [2] A centrifugal apparatus is one which rotates rotors holding samples at high speed to apply a large centrifugal acceleration to the samples, so that high-density sample components can be placed on an outer layer in a radial direction and low-density sample components can be placed on an inner layer in a radial direction to separate the components from each other. An automatic balancing centrifugal apparatus is one, which calculates load differentials of each bucket, which inevitably occur due to the number of samples or the load differentials of each sample held in each bucket, and the like, and automatically maintains a balance before centrifugation.

[3]

- [4] Fig. 1 is a schematic perspective view of a conventional automatic balancing centrifugal apparatus by lever movement. As shown in Fig. 1, the conventional automatic balancing centrifugal apparatus by lever movement comprises a centrifuge motor (2); a rotor (20) which is axially bonded to the centrifuge motor (2) to be rotated; a rotor lever (22) which rotates while supporting buckets (40) and is supported so as to be capable of being horizontally moved with respect to the rotor (20); an elevator-type load measurement mechanism (hereinafter "load measurement mechanism") which measures the loads of both buckets (40) before centrifugation in order to sense the load unbalance of both buckets (40); a slip ring (50) which is fixed in a given place to a centrifuge motor shaft (4) and extends from the power lines and signal lines of electrical/electronic components within the rotor (20) to be exposed to the outside; and a wiring terminal carrier (60) which extends from the external power lines and signal lines and mounts a wiring terminal (not shown) disposed in one-to-one correspondence with the slip ring (50) to contact and separate with respect to the slip ring (50). Reference numeral 22A indicates bucket support arms formed on the rotor lever (22), and reference numeral 42 indicates a locking groove which is formed on the bucket (40) and is locked in the bucket support arms (22A). Meanwhile, the con-

ventional automatic balancing centrifugal apparatus by lever movement may further comprise a position sensor (not shown) for positioning the bucket (40) right above the load measurement mechanism (30).

[5]

[6]

In the above-described constitution, an operator lifts a loading plate of the load measurement mechanism (30) before each centrifugation while positioning one bucket (40) right above the load measurement mechanism (30). Then, the operator measures the load of the bucket (40) while the bucket (40) is released with respect to the rotor lever (22), and the operator lowers the loading plate and measures the load of another bucket (40) in the same manner, thereby measuring a load differential between both buckets (40). Thereafter, in order to keep a dynamic balance among samples in the buckets (40) at the time of rotation for centrifugation, a lever carrying motor (not shown) mounted within the rotor (20) is driven to thereby adjust a differential in distance between the bucket (40) and the rotor rotation shaft which corresponds to the load differential of the buckets (40), thereby making centrifugal forces applied to the samples at both ends uniform. To do this, the wiring terminal carrier (60) is moved forward to supply required power and control signals to the lever carrying motor while being in contact with the slip ring (50). Then, the wiring terminal carrier (60) is moved backward to be separated from the slip ring (50). The overall constitution or individual constitutions of the automatic balancing centrifugal apparatus by lever movement are specifically disclosed in Korean Patent No. 343336, entitled "Automatic balance adjusting centrifuge apparatus"; Korean Patent Application No. 2002-17498, entitled "Automatic balance adjusting centrifuge apparatus"; Korean Patent Application No. 2004-26526, entitled "Elevator-type load measurement apparatus"; Korean Patent Application No. 2004-76489, entitled "Automatic balancing rotor for centrifuges"; and Korean Patent Application No. 2004-76490, entitled "Signal transfer apparatus of a rotating body," filed by the same applicant, and the explanations thereof in detail will be omitted here. All patents and patent applications mentioned herein are incorporated herein by reference.

[7]

[8]

However, the above-described conventional automatic balancing centrifugal apparatus by lever movement needs a very precise lever carrying mechanism as well as a slip ring being a non-contact electrical connection and an external wiring terminal carrying mechanism in order to supply power or signals to the lever transfer motor. Due to such complex mechanism and electrical characteristics, the conventional automatic balancing centrifugal apparatus by lever movement has a limited durability compared to a typical centrifugal apparatus without automatic balancing function; there is a limit in processing a large quantity of samples due to a limited bucket in-

stallation; and there is a problem which cannot centrifuge a sample according to various high-speed rotation conditions.

## **Disclosure of Invention**

### **Technical Problem**

- [9] The present invention aims to solve these problems of the prior art and to provide an automatic balancing centrifugal apparatus by fluid compensation, which compensates a load unbalance among buckets holding samples by injecting a fluid into the buckets or sucking the fluid from the buckets, thereby simplifying the overall structure of the centrifugal apparatus, increasing the durability, and centrifuging a large quantity of samples under various high-speed rotation conditions smoothly.

### **Technical Solution**

- [10] In order to achieve the above object, an automatic balancing centrifugal apparatus by fluid compensation according to the present invention comprises:
- [11]
- [12] (a) rotors on which plural buckets are mounted;
- [13] (b) a centrifuge motor for rotating said rotors;
- [14] (c) a load measurement mechanism, which is installed so as to lift and lower along the rotation trace of said buckets;
- [15] (d) a position sensing mechanism for sensing whether or not each of said buckets is positioned right above said load measurement mechanism;
- [16] (e) a fluid compensation mechanism for injecting a fluid into said buckets or sucking the fluid from said buckets; and
- [17] (f) a main control part for controlling the overall operations of each of said elements and controlling said fluid compensation mechanism so that the loads of said buckets can be equal to each other.

### **Brief Description of the Drawings**

- [18] Fig. 1 is a schematic perspective view of a conventional automatic balancing centrifugal apparatus.
- [19]
- [20] Fig. 2 is a schematic perspective view of an automatic balancing centrifugal apparatus by fluid compensation according to the present invention.
- [21]
- [22] Fig. 3 is a schematic sectional view of a fluid compensation mechanism taken along line A-A of Fig. 2.
- [23]
- [24] Fig. 4 is an electric block diagram of an automatic balancing centrifugal apparatus by fluid compensation according to the present invention.

[25]	
[26]	<Description of the main reference number in the drawings>
[27]	100 centrifugal apparatus
[28]	112 centrifuge motor
[29]	102 motor shaft
[30]	110 motor top plate
[31]	111 bucket positioning sensor
[32]	112 rotational speed sensor
[33]	113 slit disc
[34]	120 rotor
[35]	130 load measurement mechanism
[36]	131 vertical support
[37]	132 elevation motor
[38]	133 loading plate
[39]	134 photocoupler
[40]	135 position indicating marker
[41]	136 linear motion guide
[42]	140 bucket
[43]	141 sample holding plate
[44]	141A sample holding hole
[45]	142 sample cylinder
[46]	150 fluid compensation mechanism base
[47]	160 fluid storage tank
[48]	161 fluid feeding inlet
[49]	162 fluid sucking hole
[50]	163 fluid exhaust outlet
[51]	171 exhaust pump
[52]	172 sucking pump
[53]	173 connection tube
[54]	174 nozzle
[55]	180 elevation motor
[56]	182 nozzle support
[57]	183 elevation plate
[58]	184 slide center
[59]	185 linear bush
[60]	186 linear motion guide
[61]	187 screw shaft
[62]	188 position indicating marker

- [63] 188U upper limit indicating slit
- [64] 188L lower limit indicating slit
- [65] 189 photocoupler
- [66] 200 main control part
- [67] 202 key input part
- [68] 204 speed sensing part
- [69] 206 bucket positioning sensing part
- [70] 208 indicating part
- [71] 210 entrifuge motor drive part
- [72] 212 centrifuge motor
- [73] 220 load measurement part
- [74] 222 position sensing part
- [75] 224 load sensor
- [76] 226 elevation motor drive part
- [77] 228 elevation motor
- [78] 230 fluid compensation part
- [79] 232 position sensing part
- [80] 233 elevation motor
- [81] 234 elevation motor drive part
- [82] 236 pump drive part
- [83] 238 pump
- [84]
- [85]

### **Mode for the Invention**

- [86] Hereinafter, an automatic balancing centrifugal apparatus by fluid compensation according to preferred embodiments of the present invention will be explained in detail with reference to the accompanying drawings.

[87]

- [88] Fig. 2 is a perspective view showing a schematic constitution of an automatic balancing centrifugal apparatus by fluid compensation according to the present invention. Fig. 3 is a schematic sectional view of a fluid compensation mechanism taken along line A-A of Fig. 2. As shown in Figs. 2 and 3, the centrifugal apparatus by fluid compensation of the present invention may comprise: rotors (120) on which a plurality of buckets (140) are mounted; a centrifuge motor (101) for rotating said rotors (120); a load measurement mechanism (130) which is fixed in a given place and measures the loads of the buckets (140) in a predetermined order; a position sensing mechanism for sensing whether or not the buckets (140) are positioned at a pre-

determined stationary position, that is, right above the load measurement mechanism (130); and a fluid compensation mechanism which is fixed at a space above the buckets (140) and which injects a fluid into the buckets (140) or sucks the injected fluid from the buckets (140).

[89]

[90] In the above-described constitution, the rotors (120) are axially connected at the center thereof with the motor shaft (102), and may comprise either even or odd numbers of rotor arms supporting the buckets (140). However, in either case, each of the rotor arms is preferably formed so as to have the same length from the center of the motor shaft and to be conformal to each other. Reference numeral 110 represents a top plate of the centrifuge motor on which the various necessary components are mounted.

[91]

[92] The load measurement mechanism (130) may be embodied as an elevator-type load measurement mechanism as described above, and the loading plate (133) may be installed so as to be positioned right below the rotation trace of the buckets (140). The load measurement mechanism (130) may comprise: an elevation motor (132) for lifting the loading plate (133) toward the buckets (140); a vertical support (131) for supporting the elevation motor (132) and remaining components; a slide center (not shown) which is fixed to the center portion of the loading plate (133) while being screwed to the screw rotation shaft (not shown) of the elevation motor (132) by a female screw formed at the center of the slide center; a linear motion guide (136) for guiding a linear motion of the loading plate (133); a load sensor (not shown) for measuring the load applied to the loading plate (133); a position indicating marker (135) on which slits (not shown) indicating the uppermost and lowermost positions of the loading plate (133) are formed; and a photocoupler (134) which comprises a light emitting element and a photodetector, which are installed on opposite sides of a groove into which the distal end with slits of the position indicating marker (135) is interposed.

[93]

[94] The position sensing mechanism may comprise a slit disc (113), which is axially bonded with the motor shaft (102) and in which slits indicating the positioning of each of the buckets (140) are formed on the circumference thereof in a radial direction, and a bucket positioning sensor (111) which comprises a photocoupler including a light emitting element and a photodetector, which are installed on the opposite sides of a groove into which the circumference of the slit disc (113) is interposed. A plurality of slits for measuring velocity are formed on the circumference of the slit disc (113) in a radial direction. The position sensing mechanism further includes a rotational speed sensor (112) comprising a photocoupler for sensing the velocity. In this case, po-



sitioning slits must be formed in at least the same number of that of the buckets (140), and velocity measurement slits are formed in more than the number of the positioning slits. Preferably, the length of the positioning slits is formed longer than that of the velocity measurement slits in order to differentiate both from each other.

[95]

[96] The buckets (140) may be formed as a cylindrical body having a closed bottom surface, and a sample holding plate (141) for holding sample cylinders is mounted within the buckets (140). The sample cylinders (142) are inserted into a plurality of sample holding holes (141A) of the sample holding plate (141) to be supported, and a nozzle opening (not shown), through which a nozzle, as will be described below, enters and exits, is formed at the center of the sample holding plate (141).

[97]

[98] The fluid compensation mechanism may comprise a base (150) on which components thereof are mounted; a fluid storage tank (160) which is fixed on the base (150) and in which a fluid is stored; a nozzle (174) which enters and exits said buckets to inject the fluid into the buckets (140) or suck the injected fluid from the buckets (140); a nozzle support (182) for supporting the nozzle (174) so as to be positioned at the middle of the buckets (140); an elevation plate (183) which lifts and lowers while supporting the nozzle support (182); a linear motion guide (186) and a linear bush (185) for guiding an up-and-down motion of the elevation plate (183) smoothly; an elevation motor (180) which is fixed on the base (150); a screw shaft (187) which is axially connected with the elevation motor (180); a slide center (184) which is fixed at the center of the elevation plate (183) and which is screwed with the screw shaft (187) by a female screw formed on the inner circumferential surface thereof; a position indicating marker (188) on which slits (188U, 188L) indicating the uppermost and lowermost positions of the movement of the elevation plate (183); a photocoupler (189) for the position sensor which is fixed on the elevation plate (183) and which comprises a light emitting element and a photodetector, which are installed on opposite sides of a groove into which the distal end with slits of the position indicating marker (188) is interposed. The fluid storage tank (160) has a fluid feeding inlet (161) in a given place, for example, on the top surface thereof, a fluid exhaust outlet (163) on a lower part of a side surface thereof, and a fluid sucking hole (162) on an upper part of the side surface thereof. In addition, the sucking hole (162) is connected to a sucking pump (172), and an exhaust pump (171) is connected to the fluid exhaust outlet (163).

[99]

[100] In the above-described constitution, the center of the loading plate (133) of the load measurement mechanism (130) and the nozzle (174) of the fluid compensation mechanism are preferably located on the same vertical line. A reflective photocoupler

type, a magnetic detection type, that is, a magnet and reed switch type, a potentiometer type, or a variable resistor type, and the like may be adopted by substituting the photocouplers for the slit disc (113) and the bucket positioning sensor (111) of the position measurement mechanism, and the photocouplers (134, 189) for the position indicating markers (135, 188) for measuring the positions which are installed respectively at the load measurement mechanism (130) and the fluid compensation mechanism.

Furthermore, instead of using the exhaust pump (171) and the sucking pump (172), a single reversible pump, which integrates the two pumps, may be used. In such case, the fluid sucking hole, the fluid exhaust outlet, the connection tube, and the like can be integrated into one piece. Reference numeral "173" denotes the connection tube which connects the exhaust pump (171) and the sucking pump (172) to the nozzle (174).

[101]

[102] Fig. 4 is an electrical block diagram of the automatic balancing centrifugal apparatus by fluid compensation according to the present invention. For the sake of easier understanding, equivalent components in Figs. 2 and 3 have been given different reference numerals. As shown in Fig. 4, the automatic balancing centrifugal apparatus by fluid compensation may comprise a key input part (202) for inputting or selecting various functions required for the apparatus; a speed sensing part (204) for sensing the rotational speed of the buckets (140); a bucket position sensing part (206) for sensing the setup position of the buckets (140); a display part (208) for displaying the input indication or the operating state; a centrifuge motor (212) and a drive part (210) thereof; a load measurement part (220) that is an electrical configuration of the load measurement mechanism (130); a fluid compensation part (230) that is an electrical configuration of the fluid compensation mechanism; a main control part (200) for generally controlling each of the components.

[103]

[104] In the above-described constitution, the centrifuge motor (210) may adopt either an AC or DC motor having a speed control function and an electrical braking function, or a servo motor capable of controlling the speed and position. The speed sensing part (204) may comprise the speed sensor (112) and the peripheral circuit components thereof. The bucket positioning sensing part (206) may comprise the bucket positioning sensor (111) and the peripheral circuit components thereof. The display part (208) may consist of typical LEDs for displaying numbers or states or image displays such as CRTs or LCDs. The load measurement part (220) may comprise a position sensing part (222), which consists of the photocoupler (134) and the peripheral circuit components thereof, and a load sensing part (224) for sensing the load applied to the loading plate (133), and preferably, a piezoelectric sensor, an elevation motor (228) and the drive part (226) thereof. Likewise, the fluid compensation part (230) may

comprise the position sensing part (232), which consists of the photocoupler (289) and the peripheral circuit components thereof, an elevation motor (234) and the drive part (233) thereof, the exhaust pump and the sucking pump (238) (or a reversible pump) and the drive part (236) thereof.

[105]

[106] Hereinafter, the operation of the automatic balancing centrifugal apparatus by fluid compensation according to the present invention will be explained in detail for a case where four buckets are used, but not restricted thereto.

[107]

[108] Firstly, the centrifuge motor rotates to position a bucket (a) above the loading plate (133) of the load measurement mechanism (130) by a sensing signal from the bucket positioning sensing part (206). The loading plate (133) of the load measurement mechanism (130) is raised up to the upper limit by a sensing signal from the position sensing part (222), and the load of the buckets (140) is measured by the load measurement part (224) while the restraint of the buckets (140) is released from the rotor arm. After the measured load is stored in a data memory(not shown) embedded in the main control part (200), the loading plate (133) is again lowered down to the lower limit by a sensing signal from the position sensing part (222). Subsequently, the centrifuge motor (212) rotates to position a bucket (c), which is axially symmetric with the bucket (a), exactly above the loading plate (133) of the load measurement mechanism (130) by a sensing signal from the bucket positioning sensing part (206). The load of the bucket (c) is measured in the same manner as the bucket (a) to be then stored in the data memory, and then the load differential between the two buckets (a, c) is calculated.

[109]

[110] After the load differential is calculated, the elevation plate (183), that is, the nozzle (174), is lowered by the elevation motor (234) while the bucket of a smaller load is put on the loading plate (133), and the exhaust pump (238) is activated to introduce a fluid into the bucket (140) at an amount equivalent to the load differential while the load sensing part (224) senses the load of the bucket. The remaining two buckets (b, d) are compensated for the load differential in the same manner. Meanwhile, in a case where an odd number of buckets are used, after the load of each bucket is measured one after another, the remaining buckets are compensated a fluid equivalent to the load differential based on the heaviest bucket.

[111]

[112] If the loads of all the buckets are equal to each other, the centrifuge motor (212) rotates to perform centrifugation. After the centrifugation is completed, the sucking pump (238) is actuated to suck all the fluid injected into each of the buckets (140) back

to the fluid storage tank (160). Lastly, the centrifuged sample cylinders (142) are drawn out of each of the buckets (140), so the centrifugation processes are terminated.

[113]

[114] The present invention is not limited to the embodiment disclosed but may be varied and modified within the scope of the following claims.

[115]

### **Industrial Applicability**

[116]

As described above, the centrifugal apparatus of automatic balancing type by fluid compensation of the present invention does not need a slip ring since the rotor consists of a simple mechanism. Accordingly, the overall configuration of the centrifugal apparatus is simplified and the durability thereof is increased. Furthermore, since the structure of the rotor becomes slim, the rotor can mount a large quantity of or a plurality of buckets, and thus a relatively large number of samples can be processed at one centrifugation.

## Claims


- [1] An automatic balancing centrifugal apparatus by fluid compensation, comprising:
- (a) rotors on which a plurality of buckets are mounted;
  - (b) a centrifuge motor for rotating said rotors;
  - (c) a load measurement mechanism, which is installed so as to lift and lower within the rotation trace of said buckets;
  - (d) a position sensing mechanism for sensing whether or not each of said buckets is positioned above said load measurement mechanism;
  - (e) a fluid compensation mechanism for injecting a fluid into said buckets or sucking the fluid from the buckets; and
  - (f) a main control part for controlling the overall operations of each of said elements and controlling said fluid compensation mechanism so that the loads of said buckets can become equal to each other.
- [2] The automatic balancing centrifugal apparatus by fluid compensation according to claim 1, wherein the arms of said rotors have the same length from the center of a shaft and to be conformal to each other.
- [3] The automatic balancing centrifugal apparatus by fluid compensation according to claim 1, wherein said load measurement mechanism comprises:
- (a) a loading plate to which the load of said buckets are applied;
  - (b) an elevation motor for lifting or lowering said loading plate toward said buckets (140);
  - (c) a screw rotation shaft which is axially connected with said elevation motor;
  - (e) an elevation shaft for supporting said loading plate with being screwed to said screw rotation shaft;
  - (f) a linear motion guide means for guiding a up-and-down motion of the loading plate;
  - (g) a load sensor for measuring the load applied to the loading plate; and
  - (h) position sensing means for sensing the uppermost and lowermost positions of the loading plate.
- [4] The automatic balancing centrifugal apparatus by fluid compensation according to claim 1, wherein said fluid compensation mechanism comprises:
- (a) a fluid storage tank in which a fluid is stored and a fluid opening are formed in a given place;
  - (b) a nozzle which injects the fluid into said buckets or sucks the fluid from said buckets;
  - (c) pumping means which is connected to said fluid opening to exhaust the fluid

to the nozzle or to suck the fluid from the nozzle;  
(d) a connection tube for connecting said pumping means with said nozzle;  
(e) a nozzle support for supporting said nozzle so as to be positioned at the middle of said buckets;  
(f) an elevation plate which elevates and lowers while supporting said nozzle support;  
(g) a linear motion guide means for guiding an up-and-down motion of said elevation plate smoothly;  
(h) an elevation motor which is fixed on a base;  
(i) a screw shaft which is axially connected with said elevation motor;  
(j) a slide center which is fixed at the center of said elevation plate and which is screwed with said screw shaft; and  
(k) position sensing means for sensing the uppermost and lowermost positions of the movement of said elevation plate (183).

- [5] The automatic balancing centrifugal apparatus by fluid compensation according to claim 4, wherein said buckets are formed as a cylindrical body with the lower surface closed, a plurality of sample holding holes for holding sample cylinders being formed within said buckets and a nozzle opening, through which a nozzle enters and exits, being formed at the center of said buckets.
- [6] The automatic balancing centrifugal apparatus by fluid compensation according to claim 5, wherein said pumping means is a single reversible pump capable of sucking and exhausting the fluid.
- [7] The automatic balancing centrifugal apparatus by fluid compensation according to claim 6, wherein the center of said loading plate and said nozzle are located on the same vertical line.
- [8] The automatic balancing centrifugal apparatus by fluid compensation according to any one of claims 1-7, wherein said position sensing mechanism comprises a slit disc, which is axially connected with the middle of the motor shaft and in which slits indicating the positioning of each of the buckets are formed on the circumference thereof in a radial direction, and a bucket positioning sensor which comprises a photocoupler including a light emitting element and a photodetector, which are installed on the opposite sides of a groove into which the circumference of the slit disc is interposed.
- [9] The automatic balancing centrifugal apparatus by fluid compensation according to claim 8, wherein a plurality of slits for measuring the rotational speed of said buckets are formed on the circumference of said slit disc in a radial direction; said apparatus further includes a photocoupler for measuring the velocity, which comprises a light emitting element and a photodetector, which are installed on

opposite sides of a groove into which the circumference of said slit disc is interposed; and said main control part controls the rotational speed of said centrifuge motor based on a sensing signal from said photocoupler.


[Fig. 1]







[Fig. 4]



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/KR2005/003065**A. CLASSIFICATION OF SUBJECT MATTER****IPC7 B04B 5/02**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC7 B04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
Korean patents and applications for inventions since 1975: IPC as aboveElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
Delphion and keywords: centrifug\*, balanc\*, auto\* and similar terms**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02/083317 A1 (HANLAB CORPORATION) October 24, 2002 abstract, claim 1	1-9
A	US 4671940 (ABBOTT LABORATORIES) June 9, 1987 abstract, fig 1-6, column line 59 - column 6 line 57	1-9
A	US 6589789 B1 (QUEST DIAGNOSTICS INCORPORATED) July 8, 2003 claim 2, column 6 line 15-52	1-9
A	WO 03/000380 A1 (MEDICEPT, INC) January 3, 2003 abstract, fig 1-2, page 11 line 32 - page 12 line 16	1-9
A	JP 02657184 B2 (NAGASE INTEGURETSUKUSU KK) September 24, 1997 claim 1-3	1-9



Further documents are listed in the continuation of Box C.



See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

28 NOVEMBER 2005 (28.11.2005)

Date of mailing of the international search report

**29 NOVEMBER 2005 (29.11.2005)**

Name and mailing address of the ISA/KR

Korean Intellectual Property Office  
920 Dunsan-dong, Seo-gu, Daejeon 302-701,  
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

LEE, HYUN SONG

Telephone No. 82-42-481-8296



**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

PCT/KR2005/003065

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W002083317A1	2002-10-24	US6949063	2005-09-27
		US20040018927A1	2004-01-29
		KR2029049A	2002-04-17
		KR1067837A	2001-07-13
		JP2004519327T2	2004-07-02
		ES2235012T3	2005-07-01
		EP1370363B1	2005-01-26
		EP1370363A4	2004-05-06
		EP1370363A1	2003-12-17
		DE60202750C0	2005-03-03
		CN1500010A	2004-05-26
		CA2442736AA	2002-10-24
		AT0287767E	2005-02-15
US4671940	1987-06-09	JP61216758A2	1986-09-26
		EP0195321B1	1990-01-24
		EP0195321A3	1986-12-10
		EP0195321A2	1986-09-24
		DE3668425C0	1990-03-01
		CA1259974A1	1989-09-26
US6589789	2003-07-08	US6586255B1	2003-07-01
W003000380A1	2003-01-03	W00197943A1	2001-12-27
		US20020082153A1	2002-06-27
		US20020020680A1	2002-02-21
		US6605223	2003-08-12
JP02657184B2	1997-09-24	JP01301061A2	1989-12-05

**PUB-NO:** WO2006054828A1  
**DOCUMENT-IDENTIFIER:** WO 2006054828 A1  
**TITLE:** AUTOMATIC BALANCING  
CENTRIFUGAL APPARATUS BY  
FLUID COMPENSATION  
**PUBN-DATE:** May 26, 2006

**INVENTOR-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
KIM, HAK CHUL	KR
PARK, CHONG TAE	KR

**ASSIGNEE-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
HANLAB CORP	KR
KIM HAK CHUL	KR
PARK CHONG TAE	KR

**APPL-NO:** KR2005003065  
**APPL-DATE:** September 15, 2005

**PRIORITY-DATA:** KR20040094893A (November 19, 2004)

**EUR-CL (EPC):** B04B009/14

**ABSTRACT:**

CHG DATE=20060602 STATUS=O>The invention relates to an automatic balancing centrifugal apparatus by fluid compensation,

which compensates a load imbalance among buckets holding samples by injecting a fluid into the buckets or sucking the fluid from the buckets, thereby simplifying the overall structure of the centrifugal apparatus, increasing the durability, and centrifuging a large quantity of samples under various high-speed rotation conditions smoothly. The automatic balancing centrifugal apparatus by fluid compensation comprises: rotors on which a plurality of buckets are mounted; a centrifuge motor for rotating said rotors; a load measurement mechanism, which is installed so as to lift and lower along the rotation trace of said buckets and which measures the load of said buckets while the restraint of the buckets is being released at the time of lifting; a position sensing mechanism for sensing whether or not each of said buckets is positioned right above said load measurement mechanism; a fluid compensation mechanism for injecting a fluid into said buckets or for sucking the fluid from the buckets; and a main control part for controlling the overall operations of each of said elements and for controlling said fluid compensation mechanism so that the loads of said buckets can become equal to each other.